

Spectrum

Sealer/Finish

Spectrum is a sealer/finish that provides excellent durability, high initial gloss, and wet look response to ultra high-speed maintenance. UL Classified.

Directions for Use

APPLICATION: Remove all dirt and old finish by using a floor machine. Rinse floor thoroughly and allow to dry. Apply **Spectrum** in medium to heavy, uniform coats with a finish mop. Let dry thoroughly (30 minutes or longer under adverse conditions) before applying a second coat. Usually, no more than four (4) coats are necessary. Maximum of 8 coats in 24 hours. Do not pour unused product back into container.

MAINTENANCE: Dust mop, damp mop, or sweep as necessary. **Spectrum** can be buffed as soon as it is dried. However, for best results, allow to cure 24 hours before ultra high speed buffing. Dry buff as necessary, using propane, battery, or other ultra high speed buffing equipment. Buff only with ultra high speed buffing pads. Maintain/repair traffic areas with finish applications as necessary following appropriate surface preparation (buffing, dust mopping, top scrubbing).

Safety Reminder

Consult product label and Safety Data Sheet (SDS) before use. SDS's may be downloaded from www.gatorchemical.com.

Technical Specifications

Color	White
Scent	Acrylic
Foaming	N/A
Solubility in Water	Complete
Density (lb/gal)	8.65
Flash Point	None
pH	8.5

Packaging

4 x 1 Gallons
5 Gallons
15 Gallons
55 Gallons

Gator Chemical
2202 Industrial Blvd
Sarasota FL, 34234
800-234-3672
www.gatorchemical.com

